# **TECHNICAL REQUIREMENTS FOR SEALS AND STAMPS**

## RUBBER ORDINARY / FLASH SEALS



### **RUBBER ORDINARY**



#### seal

stamps are round and have legal information -TIN, OGRN



#### 

РИЛИМАФ.О.И\_\_\_\_\_

### stamp

can be framed or not framed



## facsimile

signature



#### bookmark

does not contain any legal information, most often logos or other graphic elements

## ФЛЭШ-ПЕЧАТИ (МНОГОЦВЕТНЫЕ)



#### seal

may have more than 1 color, the distance between the colored elements is not less than 5 mm



#### stamp

may have more than 1 color, the distance between the colored elements is at least 5 mm



# seals with large fillings

for prints of this type it is required to offer flash printing technology: ability to fill large areas with color



#### LAYOUT IS GIVEN INTO PRODUCTION UNDER THE FOLLOWING RULES:



- **1.** File Format COREL DRAW ONLY (not higher than version 16). ONLY VECTOR LAYOUT (no raster images)
- 2. Fonts must be converted into curved objects, and outlines converted into objects!
  Lines and objects should not
  intersect! use the tool of shaping and combine all intersecting elements into a single object.
  The minimum font size is 4pt, the minimum line thickness is 0.2mm
- **3.** For rubber stamps: layout is grouped, layout color is black. Rubber stamps do not have color filling. There is a choice of accessories in which there is a stamp pad that is already filled with blue ink (standard stamps) automatic and metal for extra cost. Standard plastic equipment is included in the price, but it is not equipped with a pillow or ink, equipped with a cover.
- **4.** For flash prints: layout is grouped, layout color is in accordance with the filling of colors, distance between the color elements is at least 5 mm. The client can order flash printing as one-color or with several colors, 1 color is included in the price, each subsequent one for an extra charge. Equipment is included in the price, they are specialized for this technology, there can be no other equipment!
- 5. Seal / stamp / bookplate / facsimile layout should be 2 mm smaller than tooling.
- **6.** Seal on the print is drawn one to one, without magnifications, distortions, otherwise the meaning of the print will be lost.
- 7. If the layout has large fill areas, then this is applicable in flash prints. In ordinary rubber seals with such layouts there will be glimpses and
- this will be considered a defect. Therefore, in this situation, offer a flash printing service.
- **8.** Microtext is not less than 4pt., most often goes along the outer circle with the overlay on the filler part of the circle. NEVER cut it from this area, but simply use as a separate object, filled with white color.

FOR MAKING A PRINT OF A DOCTOR, A CLIENT EDUCATION DOCUMENT IS REQUIRED. FOR MAKING PRINTS FOR STATE STRUCTURES, A WRITTEN APPLICATION FOR THE NAME OF OUR COMPANY IS REQUIRED - SEND TO PRODUCTION AND AGREE. WE DO NOT MAKE SEALS WITH SYMBOL OF THE STATE COAT OF ARMS OF RUSSIA (DOUBLE-HEADED EAGLE)